

3MM PREMIUM RED VAPOUR SEAL UNDERLAY

Whiteriver

wood for living

HIGH DENSITY POLYETHYLENE UNDERLAY WITH ENHANCED IMPACT SOUND REDUCTION.
INTEGRATED VAPOUR BARRIER WITH BUILT IN OVERLAP TAPE FOR FAST AND EASY INSTALLATION.
SUITABLE FOR RESIDENTIAL & COMMERCIAL USE.

100% Recyclable, CFC & HCFC Free

3mm x 1m x 10m (10m² Roll)

Quantity per roll :	10m ²
Roll Size :	3mm x 1m x 10m
TOG Rating:	0.60
Sound Improvement :	19dB
Underfloor Heating Y/N :	With laminate only
Compressive Strength :	Excellent
Heat Transfer Resistance:	0.06 k/w m ²
Thermal Insulation :	Medium
Protection Against Moisture:	>75m
Density :	100kg / m ³
Product Code:	F1010050



- **SIGNIFICANTLY REDUCES NOISE FROM WOODEN AND LAMINATE FLOORING**
- **HELPS TO LEVEL OUT ANY MINOR UNEVENNESS IN THE SUBFLOOR**
- **PREVENTS OVERSTRAINING OF THE FLOOR BOARDS**

LAYING INSTRUCTIONS

Before starting to lay the material, take care that the sub floor is even, dry, clean and pressure resistant. 3mm Premium Red Vapour seal should be rolled onto the floor parallel to the wall with vapour barrier side down and at right angles to the direction in which you plan to lay the floor covering. It can be trimmed with a cutter or sharp knife. Joints must be overlapped and taped down using the full width of the vapour barrier border. Extend the moisture barrier up the walls behind the skirting. When the whole room has been laid, the intended floor covering (laminate, cork, prefabricated parquet etc.) can be laid on top.

